



SUNCOAST

SUNGUARD II Spray Applied Blanket Insulation

U.S. TESTING CLASSIFIED
CLASS "A" BUILDING MATERIAL
HUD FHA/VA APPROVED

We recommend Sun-Guard II S.A.B. be installed to these specifications to achieve the stated thermal resistance (R-Value). TYPE-Spray Applied Blanket Cellulose Insulation.

R-Value	Minimum Thickness	Maximum Yield Per Bag	Maximum Bags Per 1000 Sq. Ft.	Minimum Installed Weight Per Sq. Ft.
11	3.0	101.7	9.8	0.34
13	3.5	86.0	11.6	0.41
19	5.1	58.8	17.0	0.60
24	6.5	46.5	21.5	0.75
26	7.0	42.9	23.3	0.82
30	8.1	37.2	26.9	0.94
32	8.7	35.0	28.7	1.00
38	10.3	29.4	34.0	1.19
40	10.8	27.9	35.8	1.25

Based on 1.4 lbs. per cu. ft. applied density, nominal bag weight of 35 lbs. (net area). R-Value determined in accordance with HUD Use of Materials Bulletin #80.

SPRAY APPLIED BLANKET

WALL INSTALLATION

CEILING INSTALLATION

THICKNESS _____

8.1

R-VALUE _____

30

BAGS _____

68

DATE _____

4-16-93

INSTALLED BY _____

CENTRAL VALLEY INSULATION

SIGNATURE _____

[Handwritten Signature]

BUILDER _____

SIGNATURE _____



SUNCOAST INSULATION COMPANIES

3890 E. Craig Road
N. Las Vegas, Nevada 89030

1928 Smith