



DESIGN PRESSURE = 150 P.S.I.

WELD ALL JOINTS

- NOTES:**
1. CONNECT 5KV CABLE TO EXISTING 5KV CABLE AT THE PULLBOX.
  2. SEE DIVISION 37 OF SPECIFICATIONS REGARDING TESTING AND DISINFECTION. THE CONTRACTOR SHALL INSTALL A TEMPORARY BUMPED HEAD WITH OUTLET. REMOVE BUMPED HEADS AND CONNECT TO EXISTING PIPE IN ACCORDANCE WITH DETAIL 1 ON SHEET 16.

Avoid cutting underground utility lines. If you dig, call before you dig.  
 1-800-227-2600  
 UNDERGROUND SERVICE ALERT (USA)

LAS VEGAS VALLEY WATER DISTRICT

G. C. WALLACE, INC.  
 Engineering/Architecture  
 1555 SOUTH RAINBOW BLVD./LAS VEGAS, NEVADA 89102

VERIFY SCALE  
 1/2" = 0' 1/2"

3205 ZONE RESERVOIR INLET/OUTLET PIPELINE  
 ALTA DRIVE  
 PLAN & PROFILE  
 STA 41+50 TO STA 51+94.75

SCALE  
 HORIZ. SCALE = 1" = 40'  
 VERT. SCALE = 1" = 4'

CONTRACT NUMBER  
**770**  
 DRAWING NUMBER C4  
 SHEET 7 OF 19

565-283

