



Technical drawing illustrating the corner detail of a suspended ceiling system. The drawing shows the connection between the metal runner, metal studs, metal cross tee, and suspended acoustical ceiling tile. The G.W.B. (Gypsum Wall Board) is shown on the wall and ceiling, with a corner bead installed at the corner. The drawing is labeled with the following components:

- METAL RUNNER
• 4'-0" O.C. MAX.
- 3 5/8" MTL STUD •
16" O.C. SECURED TO
STRUCTURE ABOVE
- METAL CROSS TEE
• 24" O.C.
- SUSPENDED ACOUSTICAL
CEILING TILE
- G.W.B. w/ 4" RETURN
- CORNER BEAD
- G.W.B.

R 19 RIGID INSUL. FRAMING, SEE SHEET A92

VARIES

PROVIDE BLOCK'S AS REQ'D FOR MOUNTING OF ELECTR. FIXTURES

(L.A.M.-3) 0/ 1/2" FLYWOOD.

RAISED SOFFIT - SEE REFLECT. CLING FILM FOR STAIRING POINT DIBS.

PAINTED GYPSUM BOARD FINISH

EXIT SIGN, SEE ELECTRICAL DRAWINGS

2" EPS FOAM POPOUT ABOVE STOREFRONT

ALUMINUM TRANSOM WINDOW

PROVIDE STUCCO DRIP EDGE

[illegible]