



TYPICAL DETAILS
TENNIS COURT FENCE

FENCE CONSTRUCTION NOTIFS	
1.	CORNER, TENSION AND GATE POSTS TO BE 3 IN. O.D. PIPE 5.79 LBS/FT
2.	LINE POSTS, TOP RAIL, CENTER RAIL AND GATE FRAMES TO BE 1-5/8 IN. O.D. PIPE 2.27 LBS/FT
3.	CHAIN LINK FABRIC (9 GAUGE, 2 IN. MESH) TO BE INSTALLED ON COURT SIDE OF ALL POSTS
4.	DIAGONAL TRUSS RODS TO BE 3/8 IN. ROUND ROD 0.37 LBS/FT
5.	TENSION WIRE TO BE 7 GAUGE COIL SPRING WIRE WITH FABRIC TIE WIRES ON 18 IN. CENTERS
6.	FABRIC BANDS ON 18 IN. CENTERS HORIZONTAL BARS
7.	FABRIC BANDS ON 16 IN. CENTERS VERTICAL POSTS.
8.	STRETCHER BARS TO BE 1/4 x 3/4 IN. FLAT 0.638 LBS/FT
9.	OUTSIDE, SLEEVE-TYPE COUPLING, 7 IN. MINIMUM LENGTH SPACED AT 20 FEET CENTERS. ONE COUPLING IN EVERY FIVE TO BE SPRING LOADED, EXPANSION TYPE COUPLING
10.	PEDESTRIAN GATES TO HAVE A LATCH-TYPE LATCH WITH PROVISION FOR PADLOCK.
11.	ALL POSTS TO BE FITTED WITH ORNAMENTAL TOPS
12.	STRETCHER BAR CLAMPS ON 16 IN. CENTERS. MAXIMUM SPACING BETWEEN BARS IS 100 LIN. FT. BANDS 1/8 x 3/4 IN.
13.	CENTER RAIL REQUIRED FOR ENTIRE LENGTH OF 12 FT. STRETCH
14.	LINE POSTS TO BE EQUALLY SPACED BETWEEN CORNER, TENSION AND GATE POSTS

STATE OF NEVADA
DEPARTMENT OF HIGHWAYS

SPECIAL DETAILS

650.2