



QUALITY ESTIMATES		
121.25	15 REINFORCED CONCRETE PIPE	510 LF
200.000	CLEARING AND GRUBBING	1 LS
200.100	CONCRETE REMOVAL	210 SF
201.100	ROADWAY EXCAVATION	8,300 CY
302.100	TYPE II GRAVEL BASE	3,340 CY
334.006	3 IN ASPHALT CONCRETE PAVEMENT	3,840 SF
334.010	5 IN ASPHALT CONCRETE PAVEMENT	7,736 SF
324.503	1/2 IN ASPHALT CONCRETE ISLAND SURFACING	142 SF
340.014	L TYPE CURB AND GUTTER (24" WIDE)	181 LF
340.015	TYPE II CURB	1,850 LF
340.144	4 ISLAND CONCRETE	2,296 SF
912.203	2 FT BEEHIVE DROP INLET	3 EA
600.000	ADJUST ELEVATION OF STORM DRAIN	
600.100	ADJUST ELEVATION OF DROP INLET	1 EA
700.000	15 R.C.P CONCRETE ENCASUREMENT 10'-2"	2 CY

CONSTRUCTION PLANS

REV NO	DATE	DESCRIPTION	APPROVED

CLARK COUNTY, NEVADA
ENGINEERING DIVISION

NELLIS BLVD AND STEWART AVE
INTERSECTION
PLAN and PROFILE
(STEWART AVE)

PROJECT NO. 1212 FLD BK 404	DATES: MAR 1977	SCALE: HORIZ 1"=40'
DRAWN BY: M/V & J/H	MAR 1977	VERT 1"=4'
DESIGNED BY: S/E & S/T	MAR 1977	DRAWING NO. L-886
CHECKED BY: S/E & S/T		SHT 3 OF 5
APPROVED BY COUNTY ENGINEER		

