

SECTION VIEW A-A

SECTION VIEW B-B

VIEW C-C

TYPICAL SECTION PIPE JOINT

NOTE:

1. IF REIN. CONC. PIPE IS USED IN PLACE OF C.M.P., A 60" ϕ TO 54" ϕ REDUCER WILL BE REQUIRED AT THE JUNCTION CHAMBER.
2. HEADWALL CONCRETE TO BE 3000#-CLASS F.
3. ESTIMATED QUANTITY CONC. REQUIRED $\approx$ 27 CU. YDS.
4. REIN. STL OMITTED FROM SOME VIEWS OF DWG. FOR CLARITY.

REVISIONS			
NO.	BY	DESCRIPTION	DATE
1	AW	DESIGNED BY CRAWFORD	4-16-54
2	AW	DRAWN BY ABLES	4-17-54
3	AW	CHECKED BY HARRIS	5-2-54
4	AW	APPROVED	
5	AW	CITY ENGR.	

STAGE II CONSTRUCTION

CITY OF LAS VEGAS NEVADA

ENGINEERING DEPT.

WASHINGTON AVE. STORM SEWER

HEADWALL DETAILS- STAGE II

DESIGNED BY CRAWFORD

DRAWN BY ABLES

CHECKED BY HARRIS

APPROVED

CITY ENGR.

SCALE 3/8" = 1'-0" & NOTED

FIELD BOOK NO.

WORK ORDER NO. 1161

DRAWING NO.

327-V 45