

ABBREVIATIONS

&	AND	FDN	FOUNDATION	PRCST	PRECAST
@	AT	F.E.	FIRE EXTINGUISHER	PL.	PLATE
<	CENTERLINE	F.E.C.	FIRE EXTINGUISHER CAB.	P. LAM.	PLASTIC LAMINATE
Ø	DIAMETER OR ROUND	F.H.C.	FIRE HOSE CABINET	PLAS.	PLASTER
#	POUND OR NUMBER	FIN.	FINISH	PLYWD	PLYWOOD
ACOUS	ACOUSTICAL	FLR.	FLOOR	PR	PAIR
A.D.	AREA DRAIN	FLASH	FLASHING	PT	PAINT
ADJ.	ADJUSTABLE	FLUOR	FLUORESCENT	P.T.D.	PAPER TOWEL DISPENSER
AGGR.	AGGREGATE	F.O.C.	FACE OF CONCRETE	P.T.O./R	COMBINATION PAPER TOWEL
AL.	ALUMINUM	F.O.F.	FACE OF FINISH	DISPENSER AND RECEPTACLE	
APPROX	APPROXIMATE	F.O.S.	FACE OF STUDS	PTN	PARTITION
ARCH	ARCHITECTURAL	FFRF	FULL SIZE	P.T.R	PAPER TOWEL RECEPTACLE
ASPH	ASPHALT	FT	FOOT OR FEET		
A.V.	AUDIO / VISUAL	FTG.	FOOTING	Q.T.	QUARRY TILE
		FURR	FURRING		
		FUT	FUTURE	R	RISER
BD	BOARD			RAD.	RADIUS
BITUM	BITUMINOUS	GA.	GAUGE	R.D.	ROOF DRAIN
BLDG.	BUILDING	GALV	GALVANIZED	REF.	REFERENCE
BLK	BLOCK	G.B	GRAB BAR	REFR	REFRIGERATOR
BLK'G	BLOCKING	GL	GLASS	RSTR	REGISTER
BM.	BEAM	GND	GROUND	REIN.	REINFORCED
BOT	BOTTOM	GR	GRADE	REQ.	REQUIRED
		GYP	GYPSPUM	RESIL.	RESILIENT
				RM.	ROOM
				R.O.	ROUGH OPENING
				RWD.	REDWOOD
				R.W.L.	RAIN WATER LEADER
				S	SOUTH
				S.C.	SOLID CORE
				S.C.D	SEAT COVER DISPENSER
				SCHED	SCHEDULE
				SD.	SOAP DISPENSER
				SECT.	SECTION
				SH.	SHELF
				SHR	SHOWER
				SHT	SHEET
				SM	SIMILAR
				S.N.D.	SANITARY NAPKIN DISPENSER
				SPEC	SPECIFICATION
				SQ.	SQUARE
				SST.	STAINLESS STEEL
				S.SK.	SERVICE SINK
				STA.	STATION
				STD.	STANDARD
				STL.	STEEL
				STOR.	STORAGE
				STR.	STRUCTURAL
				SUSP	SUSPENDED
				SYM.	SYMMETRICAL
				TRD.	TREAD
				T.B.	TOWEL BAR
				TEL.	TELEPHONE
				T.E.R	TELEPHONE EQUIPMENT ROOM
				T. & G	TONGUE AND GROOVE
				THK.	THICK
				T.O.C	TOP OF CURB
				T.O.P.	TOP OF PAVEMENT
				T.O.W.	TOP OF WALL
				T.V	TELEVISION
				TYP.	TYPICAL
				UNFIN	UNFINISHED
				UN.O	UNLESS NOTED OTHERWISE
				UR.	URINAL
				VAR.	VARIES
				V.B	VAPOR BARRIER
				V.C.G.	VINYL CORNER GUARD
				VERT	VERTICAL
				VEST.	VESTIBULE
				V.T	VINYL TILE
				W	WEST
				W/	WITH
				W.C	WATER CLOSET
				WD.	WOOD
				W/O	WITHOUT
				WP.	WATERPROOF
				WSCT.	WAINSCOT
				WT.	WEIGHT
E.	EAST				
EA.	EACH				
E.J	EXPANSION JOINT				
ELEC	ELECTRIC	N.	NORTH		
EMER.	EMERGENCY	N.I.C	NOT IN CONTRACT		
ENCL.	ENCLOSURE	NO.	NUMBER		
E.P	ELECTRICAL PANELBOARD	NOM	NOMINAL		
E.P.D.M.	SINGLE PLY ROOF MEMBRANE	N.T.S.	NOT TO SCALE		
EQ	EQUAL				
EQUIP	EQUIPMENT	O.A	OVERALL		
E.W.C.	ELECTRIC WATER COOLER	OBS.	OBSURE		
EXST.	EXISTING	O.C.	ON CENTER		
EXPO.	EXPOSED	O.D.	OUTSIDE DIAMETER (DIM.)		
EXP	EXPANSION	O.F.C.I	OWNER FURNISHED, CONTRACTOR INSTALLED		
EXT.	EXTERIOR	O.F.O.I	OWNER FURNISHED, OWNER INSTALLED		
		OFF	OFF		
F.A.	FIRE ALARM	OPN'G	OPENING		
F.B.	FLAT BAR	OPP	OPPOSITE		
F.D.	FLOOR DRAIN				

FIRE NOTES

1. PROVIDE ALL FIRE EXTINGUISHERS REQUIRED BY FIRE DEPARTMENT FIELD INSPECTOR.
2. EVERY EXIT DOOR SHALL BE OPENABLE FROM THE INSIDE WITHOUT THE USE OF A KEY OR ANY SPECIAL EFFORT OR KNOWLEDGE. SPECIAL LOCKING DEVICES SHALL BE OF APPROVED TYPE. ALL NEW DOORS SHALL HAVE HANDICAPPED LEVER HANDLES.
3. DOORS OPENING INTO REQUIRED 1-HOUR FIRE RESISTIVE CORRIDOR SHALL BE PROTECTED WITH A SMOKE OR DRAFT STOP FIRE ASSEMBLY HAVING A 20-MINUTE RATING AND BE SELF-CLOSING.
4. INTERIOR WALL AND CEILING FINISHES FOR EXIT CORRIDORS SHALL NOT EXCEED AN END POINT FLAME SPREAD RATING OF 200.
5. ANY DECORATIONS (CURTAINS, DRAPES, SHADES, HANGINGS, ETC.) USED SHALL BE NON-COMBUSTIBLE OR BE FLAME-PROOFED IN AN APPROVED MANNER.
6. PROVIDE ILLUMINATED EXIT SIGNS AS PER 3314 WHERE REQUIRED.
7. PROVIDE A PORTABLE FIRE EXTINGUISHER WITH A RATING OF NOT LESS THAN 2-A OR 2-A10BC WITHIN 75 FEET TRAVEL DISTANCE TO ALL PORTIONS OF THE BUILDING ON EACH FLOOR, ALSO DURING CONSTRUCTION, SEE FLOOR PLAN FOR ADDITIONAL INFORMATION.

PARTITION NOTES

1. ALL FIRE RATED PARTITIONS INCLUDING TAPING AND FINISHING OF GYP. BOARD FACES SHALL BE IN ACCORDANCE WITH MANUFACTURER DIRECTIONS FOR ACHIEVING SPECIFIED RATING. ALL OPENINGS, GAPS, ETC. SHALL BE FILLED WITH APPROVED FIRE SATING. ALL MECHANICAL / ELECTRICAL PENETRATIONS SHALL CONFORM TO ALL CODES GOVERNING SUCH PENETRATIONS.
2. THE PARTITIONS DETAILED WITH SPECIFIC S.T.C. RATINGS AND FIRE RESISTIVE RATINGS ARE THE STANDARD TESTED SYSTEMS PUBLISHED BY UNITED STATES GYPSUM COMPANY. EXCEPT AS EXCEEDED BY THESE DRAWINGS AND THE MANUFACTURER'S PUBLISHED SPECIFICATIONS AND DETAILS TO ACHIEVE THE REQUIRED S.T.C. AND FIRE RESISTIVE RATINGS.
3. INCREASE STUD THICKNESS WHERE REQUIRED FOR HANGERS, ELECTRIC PANELS, FIRE HOSE CABINETS, PLUMBING LINES, ELECTRICAL CONDUIT AND SIMILAR ITEMS. VERIFY LOCATIONS WITH THE OTHER CONTRACTORS AND REVIEW FURRED AREAS IN ADDITION TO THOSE SHOWN ON THE DRAWINGS WITH ARCHITECT PRIOR TO INSTALLATION.
4. INSTALL BACKING PLATES AT WALLS AND CEILINGS FOR ATTACHMENT OF ALL FIXTURES, EQUIPMENT, WALL MOUNTED LIGHT FIXTURES, CHANDELIERS, CANOPIES, DRAPERY TRACKS, VALANCES, CABINETS AND SIMILAR ITEMS. THE DRYWALL CONTRACTOR IS RESPONSIBLE TO SEE THAT THE VARIOUS OTHER TRADES SUBMIT THEIR SHOP DRAWINGS AND SPECIAL DETAILS AND THE BACKING PLATES IN AMPL. TIME FOR INSTALLATION. BACKING PLATES SHALL BE 6" WIDE MINIMUM X 16 GAUGE SHEET METAL. BACKING PLATES SHALL BE LONG ENOUGH TO COVER AT LEAST 3 STUDS AND SHALL BE ATTACHED TO EACH STUD AT TOP AND BOTTOM OF PLATE.
5. PARTITIONS AND CEILINGS SHALL BE PLUMB, LEVEL AND / OR TRUE TO INTENDED LINE IN ACCORDANCE WITH TOLERANCES IN THE SPECIFICATIONS OR THE RECOMMENDED TRADE STANDARD, WHICHEVER IS MORE STRINGENT.
6. MAXIMUM ALLOWABLE PARTITION HEIGHTS ARE SHOWN ON THE DETAILS AND IN UNITED STATES GYPSUM PUBLICATIONS AND DETAILS. WHERE SPECIFIC CONDITIONS REQUIRE GREATER HEIGHTS, ANY OR ALL OF THE FOLLOWING SHALL BE DONE:
 - INCREASE STUD THICKNESS
 - DECREASE STUD SPACING, AND / OR
 - BRACE PARTITION TO THE BUILDING STRUCTURE ABOVETHE ADJACENT CEILINGS
7. DEMISING WALLS, PLENUMS, SHAFTS, 2 & 3 HOUR FIRE RESISTIVE RATED PARTITIONS AND OTHER FULL HEIGHT PARTITIONS SHALL EXTEND FROM THE FLOOR SLAB TO THE FLOOR OR ROOF SLAB ABOVE.
8. TAPE AND FILL JOINTS AND SEAL PERIMETERS OF SHAFTS AND PLENUMS SO THAT ASSEMBLIES ARE AIR TIGHT.
9. INCREASE GYPSUM BOARD THICKNESS BEHIND ELECTRICAL PANELS AS REQUIRED BY CODE.
10. ALL GYPSUM BOARD SHALL BE 5/8" TYPE "X" OR TYPE "C" - WATER RESISTANT.

GENERAL NOTES

1. THE DRAWINGS AND SPECIFICATIONS ARE PREPARED TO SHOW THE ARCHITECT'S INTENT IN THE DESIGN AND CONSTRUCTION FOR THIS PROJECT. IN ALL MATTERS RELATED TO THE USE OR INTERPRETATION OF THESE VARIOUS DRAWINGS AND SPECIFICATIONS, THE OWNER'S REPRESENTATIVE WRITTEN STATEMENT SHALL BE CONSIDERED FINAL.
2. ALL CONSTRUCTION & MATERIALS SHALL BE EQUAL TO OR EXCEED MINIMUM REQUIREMENTS OF THE CURRENT EDITIONS OF THE UNIFORM BUILDING CODE, NATIONAL ELECTRICAL CODE, AND ALL REQUIREMENTS OF THE VARIOUS GOVERNING AGENCIES.
3. ALL WORK IS TO BE COMPLETE, OPERABLE AND ACCOMPLISHED IN A NEAT AND WORKMANLIKE MANNER. IN ACCORDANCE WITH THE BEST PRACTICES OF THE VARIOUS TRADES AND TO THE SATISFACTION OF THE OWNER'S REPRESENTATIVE.
4. THE GENERAL CONTRACTOR SHALL VERIFY ALL DIMENSIONS AND SITE CONDITIONS BEFORE STARTING WORK. THE OWNER'S REPRESENTATIVE SHALL BE NOTIFIED OF ANY DISCREPANCY.
5. SHOULD A DISCREPANCY APPEAR IN SPECIFICATIONS OR DRAWINGS, OR IN WORK DONE BY OTHERS, THAT AFFECT THE WORK, NOTIFY THE GENERAL CONTRACTOR AND THE OWNER'S REPRESENTATIVE AT ONCE FOR INSTRUCTION. IF THE CONTRACTOR PROCEEDS WITH THE WORK AFFECTED WITHOUT WRITTEN INSTRUCTION FROM THE OWNER'S REPRESENTATIVE, THE CONTRACTOR SHALL BE RESPONSIBLE FOR ANY WORK RESULTING IN DAMAGE OR DEFECT.
6. SHOULD A CONFLICT OR DISCREPANCY OCCUR IN/OR BETWEEN DRAWINGS AND SPECIFICATIONS, IT IS DEEMED THAT THE CONTRACTOR HAS ESTIMATED THE MOST EXPENSIVE MATERIALS AND CONSTRUCTION INVOLVED. UNLESS HE HAS ASKED FOR AND OBTAINED WRITTEN INSTRUCTION FROM THE OWNER'S REPRESENTATIVE AS TO WHICH METHOD OR MATERIALS WILL BE REQUIRED.
7. THE GENERAL CONTRACTOR IS TO BE FAMILIAR WITH THE EXISTING JOB SITE AND CONDITIONS. HE IS TO ACCEPT THOSE EXISTING CONDITIONS AS HE FINDS THEM.
8. ALL TRADES ARE TO BE FAMILIAR WITH ALL DOCUMENTS AND INFORMATION SHOWN. INFORMATION ON ONE IS AS BINDING AND IS AS IF SHOWN ON ALL.
9. NO PORTION OF THE WORK REQUIRING A SHOP DRAWING OF SAMPLE SUBMISSION SHALL BE COMMENCED UNTIL THE SUBMISSION HAS BEEN APPROVED BY THE OWNER'S REPRESENTATIVE. ALL SUCH PORTIONS OF THE WORK SHALL BE IN ACCORDANCE WITH APPROVED SHOP DRAWINGS AND SAMPLES.
10. THE CONTRACTOR SHALL CONFINE OPERATIONS AT THE SITE TO AREAS PERMITTED BY LAW, ORDINANCES, PERMITS AND THE CONTRACT DOCUMENTS. HE SHALL NOT UNREASONABLY ENCUMBER THE SITE WITH ANY MATERIALS OR EQUIPMENT.
11. THE CONTRACTOR SHALL DO ALL CUTTING, FITTING OR PATCHING OF HIS WORK THAT MAY BE REQUIRED AND SHALL NOT ENDANGER ANY WORK BY CUTTING, EXCAVATING, OR OTHERWISE ALTERING THE WORK OR ANY PART OF IT.
12. ALL PATCHING, REPAIRING AND REPLACING OF MATERIALS AND SURFACES CUT OR DAMAGED IN EXECUTION OF WORK SHALL BE REPAIRED WITH APPLICABLE MATERIALS SO THAT SURFACES REPLACED WILL UPON COMPLETION, MATCH SURROUNDING SIMILAR SURFACES.
13. THE GENERAL CONTRACTOR SHALL MAINTAIN THE JOB SITE IN A CLEAN AND ORDERLY CONDITION, FREE OF DEBRIS AND LITTER AND SHALL REMOVE ALL TRASH AND DEBRIS AS A RESULT OF HIS OPERATION.
14. ALL MATERIAL STORED ON THE SITE SHALL BE PROPERLY STACKED AND PROTECTED TO PREVENT DAMAGE AND DETERIORATION UNTIL USED. FAILURE TO PROTECT MATERIALS MAY BE CAUSE FOR REJECTION OF WORK.
15. ALL WORK SHALL CONFORM TO THE MINIMUM STANDARDS OF THE FOLLOWING CODES:
 - THE CURRENT APPROVED EDITION OF THE U.B.C.
 - LATEST REVISION OF A.S.T.M. SPECIFICATIONS NOTED.
 - CODES AND STANDARDS LISTED IN THESE SPECIFICATIONS
 - CODES AND STANDARDS OF ANY OTHER REGULATING AGENCIES WHICH HAVE AUTHORITY OVER ANY PORTION OF THE WORK.
16. SEE ARCHITECTURAL DRAWINGS FOR THE FOLLOWING:
 - SIZE AND LOCATION OF ALL DOOR AND WINDOW OPENINGS, EXCEPT AS NOTED.
 - SIZE AND LOCATION OF ALL INTERIOR AND EXTERIOR NON-BEARING PARTITIONS
 - SIZE AND LOCATION OF ALL FLOOR AND ROOF OPENINGS EXCEPT AS SHOWN
 - FLOOR AND ROOF FINISHES.
 - STAIR FRAMING AND DETAILS, EXCEPT AS SHOWN.
 - DIMENSIONS NOT SHOWN ON THE STRUCTURAL DRAWINGS.
17. SEE MECHANICAL, PLUMBING, AND ELECTRICAL DRAWINGS FOR THE FOLLOWING:
 - PIPE RUNS, SLEEVES, HANGERS, TRENCHES, WALL AND SLAB OPENINGS, ETC. EXCEPT AS SHOWN ON NOTES.
 - ELECTRICAL CONDUCTORS, CORES OUTLETS IN WALLS AND SLABS.
 - CONCRETE INSERTS FOR ELECTRICAL, MECHANICAL OR PLUMBING FIXTURES.
 - SIZE AND LOCATION OF MACHINE OR EQUIPMENT BASES, ANCHOR BOLTS OR MOUNTS.
18. THE CONTRACT STRUCTURAL DRAWINGS AND SPECIFICATIONS REPRESENT THE FINISHED STRUCTURE. THEY DO NOT INDICATE THE METHOD OF CONSTRUCTION THE CONTRACTOR SHALL PROVIDE ALL MEASURES NECESSARY TO PROTECT THE STRUCTURE DURING CONSTRUCTION. SUCH MEASURES SHALL INCLUDE, BUT NOT BE LIMITED TO BRACING, SHORING FOR LOADS DUE TO CONSTRUCTION EQUIPMENT, ETC.
19. OPENINGS, POCKETS, ETC. LARGER THAN 6 INCHES SHALL NOT BE PLACED IN SLABS, DECKS, BEAMS, JOISTS, COLUMNS, WALLS, ETC., UNLESS SPECIFICALLY DETAILED ON THE STRUCTURAL DRAWINGS. NOTIFY THE OWNER'S REPRESENTATIVE WHEN DRAWINGS BY OTHERS SHOW OPENINGS, POCKETS, ETC., NOT SHOWN ON THE DRAWINGS, BUT NOT WHICH ARE LOCATED IN STRUCTURAL MEMBERS.
20. CONSTRUCTION MATERIALS SHALL BE SPREAD OUT IF PLACED ON FRAMED FLOORS OR ROOFS. LOAD SHALL NOT EXCEED THE DESIGN LIVE LOAD. PROVIDE ADEQUATE SHORING AND/OR BRACING WHERE STRUCTURE HAS NOT ATTAINED DESIGN STRENGTH.
21. GENERAL CONTRACTOR SHALL APPLY FOR AND OBTAIN AT THE CONTRACTOR'S SOLE EXPENSE, ALL NECESSARY CONSTRUCTION PERMITS REQUIRED BY ALL APPLICABLE BUILDING CODES AND REGULATORY CITY AND COUNTY AGENCIES.
22. EXIT SIGNS SHALL BE PROVIDED BY GENERAL CONTRACTOR PER U.B.C.
23. ACCESS PANELS SHALL BE PROVIDED FOR ELECTRICAL, PLUMBING, AND ALL OTHERS WHICH MAY BE REQUIRED.
24. INSTALL ALL MANUFACTURED ITEMS, MATERIALS AND EQUIPMENT IN STRICT ACCORDANCE WITH THE MANUFACTURER'S RECOMMENDED SPECIFICATIONS, UNLESS OTHERWISE SPECIFICALLY NOTED AND APPROVED BY THE OWNER'S REPRESENTATIVE.
25. CONTRACTOR SHALL COORDINATE THE WORK OF ALL TRADES PROVIDING WORK EQUIPMENT AND MATERIALS FOR THIS PROJECT.

DESIGN ANALYSIS

PRO-SHOP BUILDING

COVERING CODE		1997 U.B.C
OCCUPANCY GROUP(S) (U.B.C., TABLE 3-A)		M/ B
AUTOMATIC SPRINKLER SYSTEM: (SECTION 904)		REQUIRED, PROVIDED
TYPE OF CONSTRUCTION (TABLE 5-B)		V-N
FIRE RESISTANCE OF EXTERIOR WALLS FOR "M" OCCUPANCY		N.A. (TABLE 5-A).
1 HOUR, LESS THAN 5 FEET, GREATER THAN 5 FT (NONE)		
PROTECTION OF OPENINGS IN EXT. WALLS FOR "M" OCCUPANCY		N.A. (TABLE 5-A)
NOT PERMITTED LESS THAN 5 FEET		
HEIGHT & NUMBER OF STORIES (TABLE 5-B)		2 STORY, 45' MAX
	ACTUAL	1 STORY, 25 FEET.
OCCUPANCY GROUP		ALLOWABLE # OF STORIES
M		2
ALLOWABLE AREA (TABLE 5-B)		
RETAIL AREA "M"/ OFFICE "B"		8,000 S.F.
TOTAL ACTUAL AREA		
PRO SHOP AREA		1525 S.F.
UNISEX TOILET		67 S.F.
FITTING ROOM		45 S.F.
STORAGE		162 S.F.
HALLWAYS		702 S.F.
OFFICES		1433 S.F.
BREAK ROOM		165 S.F.
CONFERENCE ROOM		346 S.F.
MEN'S TOILETS/LOCKERS/SHOWERS		546 S.F.
WOMEN'S TOILETS/LOCKERS/SHOWERS		560 S.F.
JANITOR		52 S.F.
HVAC ROOM		110 S.F.
VENDING ROOM		196 S.F.
EXTERIOR STORAGE		270 S.F.
ELECTRICAL ROOM		130 S.F.
FIRE RISER ROOM		14 S.F.
TOTAL BUILDING AREA		6322 S.F.

OCCUPANCY DESCRIPTION	AREA	OCCUPANCY LOAD FACTOR	OCCUPANCY LOAD
PRO SHOP AREA "M"	1525 S.F.	30	51
FITTING ROOM	45 S.F.	50	1
OFFICES	1433 S.F.	100	15
CONFERENCE ROOM	346 S.F.	15	24
MECH / ETC / FIRE RISER	253 S.F.	300	1
VENDING	196 S.F.	50	4
TOILETS/ JANITORS	1225 S.F.	100	13
STORAGE	432 S.F.	300	2
TOTAL:			111 OCCUPANTS

RATIO CALCULATIONS FOR MIXED AREAS:
(UBC 504.3)

$$\frac{1570 \text{ S.F.} + 1779 \text{ S.F.}}{8000 \text{ S.F.} + 8000 \text{ S.F.}} = 0.2223 + 0.1962 = 0.418 < 1$$

ROOF CLASS "C" MINIMUM, "B" PROVIDED
(TABLE 15-A)

DISTANCE TO EXITS 250 FT
(SECTION 1004.2.5)

NUMBER OF EXITS:
(TABLE 10-A & SECTION 1004.2.3.4)

	REQUIRED	PROVIDED
RETAIL "M"/ OFFICE "B"	2	2

PLUMBING FIXTURES CALCULATIONS:

OFFICE "B"	WATER CLOSETS		LAVATORIES	
1779 SF / 200 = 9 (5 MALE, 5 FEMALE)	MALE	FEMALE	MALE	FEMALE
	1	1	1	1
RETAIL "M"	WATER CLOSETS		LAVATORIES	
1570 SF / 200 = 8 (4 MALE, 4 FEMALE)	MALE	FEMALE	MALE	FEMALE
	1	1	1	1
ACTUAL PROVIDED FIXTURES:	5	5	5	5

RESTROOM BUILDING

Type of Construction.	TYPE V-N
Fire Sprinklers	None
Occupancy:	
Restroom Building	B
Allowable Height	40 Feet
Actual Height	15'-0"
Allowable Number of Stories	2
Actual Number of Stories	1
Allowable Area	
8,000 SF basic one floor	
Actual Area	
Occupant Load	
Restroom/ Utility	400 SF @ 100 = 4 persons
Ext'ing Required	
Occupant load = 4 = 1 Exit Required, 3 Provided	
Fire Resistive Requirements:	
Bearing Walls - Exterior	1-HR less than 20 ft
Non Bearing Walls - Exterior	1-HR less than 20 ft
Openings	Not permitted less than 5 feet
	Protected less than 10 feet.

MATERIALS LEGEND

	FINISH WOOD		EARTH
	BLOCKING		CONCRETE
	ROUGH WOOD		MASONRY
	BATT INSULATION		METAL
	RIGID INSULATION		PLYWOOD

SYMBOL LEGEND

	DOOR NUMBER		CEILING HEIGHT
	WINDOW NUMBER		NORTH ARROW
	INTERIOR ELEVATION		KEYNOTE
	DETAIL BUBBLE		ROOM NAME AND NUMBER
	EXISTING DOOR TO REMAIN		EXTERIOR ELEVATION
	EXISTING DOOR TO BE REMOVED OR RELOCATED		DATUM REFERENCE
	NEW DOOR		
	REVISION		



REVISIONS

CONSULTANT

CDA

CREATIVE DESIGN ARCHITECTURE
ARCHITECTURE PLANNING CONSULTING
2229 Maple Road Dr. Las Vegas, NV 89134 Tel. (702) 756-6663WASHINGTON BUFFALO PARK - PHASE 1A
WASHINGTON & BUFFALO, LAS VEGAS, NVDESIGN ANALYSIS
GENERAL NOTES

STAMP

OWNER: CITY OF LAS VEGAS
DEPARTMENT OF PUBLIC WORKS
ARCHITECTURAL SERVICES400 EAST STEWART AVENUE
LAS VEGAS, NEVADA 89103
PHONE: (702) 239-5535
FAX: (702) 382-9332
TDD: (702) 386-9108

DRAWN RA

FILE GEN

DATE July-2003

SCALE NTS

BED NO 03,1534,108

CLD DWG NO 650,16-1A

SHT NO

GA-0.1

DRAWINGS AS INSTRUMENTS OF SERVICE ARE THE PROPERTY OF THE DESIGN PROFESSIONAL. WAIVER STAMP OF COPYRIGHTED APPEARS ON THE DRAWINGS AND SPECIFICATIONS ANY USE OR REPRODUCTION IN WHOLE OR IN PART WITHOUT WRITTEN CONSENT IS STRICTLY PROHIBITED. COPIES OF THE DRAWINGS AND SPECIFICATIONS RELIANCE BY THE CLIENT MAY BE UTILIZED ONLY FOR OCCUPANCY THE PROJECT FOR WHICH THEY WERE PREPARED AND NOT FOR THE CONSTRUCTION OF ANY OTHER PROJECT. N.A.C. 633.900