



PLOT PLAN.

1" = 40'-0"

LEGEND.

- NATURAL CONTOURS (EXISTING)
- NEW FINISH GRADE CONTOURS.
- T.C. — TOP OF CURB.
- B.C. — BACK OF CURB.
- F.G. — FINISH GRADE.
- B.T. — BLACK TOP (FIN. ELEV.)

NOTES.

1. ALL FILL SHALL BE COMPACTED TO 95% OF MAX. DENSITY AT OPTIMUM MOISTURE AS DETERMINED BY APPLICABLE MODIFIED A.S.T.M. STANDARDS; REMOVE 12" OF TOP SOIL UNDER ALL BUILDING AREAS, AND SCARIFY TO A DEPTH OF 6" THEN COMPACT TO 95% BEFORE PLACING FILL, TRENCHING OR PLACING CONCRETE.
2. CONTRACTOR MUST VERIFY (BY WRITTEN TEST REPORT) FILL COMPRESSION AND FILL BEARING CAPACITIES AT 1500 P.S.F. (MIN.) BEFORE
3. NO GRAVEL IS TO BE LEFT LOOSE ANYWHERE ON THE SITE.
4. ALL STEPS SHOWN ARE TO HAVE 6" RISERS AND 14" TREADS.

58-514